

| MODELS | XLB 170 | XLE 170 | XLE 170 WP | XLD 170 | XLD 170 WP | XLD 170 HS | XLD 210 | XLD 320 HS | FHS 42 PW | XLA 170 | XLA 320 | |
|---------------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|-----------------------------|----------|-----------------------------|-----------------------------|
| ARTICLE NUMBER | FA00208 | FA00218 | FA00219 | FA00016 | FA00004 | FA00412 | FA00305 | FA00432 | FA00413/21 | FA01012 | FA01013 | |
| X cut | • | • | • | • | • | • | • | • | • | • | • | |
| Y cut | • | • | • | • | • | • | • | • | • | • | • | |
| Side mark/edge following sensor | manually | • | • | • | • | • | • | • | • | • | • | |
| Square correction | | | | • | • | • | • | • | • | • | • | |
| Digitrim Mode | | | | • | • | • | • | • | | | | |
| Max. Cut thickness 0.5 mm | | | | | | | | | • | | | |
| Max. Cut thickness 1 mm | • | • | • | • | • | • | • | • | | • | • | |
| Fotoba cut mark | • | • | • | • | • | • | • | • | • | • | • | |
| Fotoba Barcode | | | | | | | | | | • | • | |
| Lenght cutting without mark | • | • | • | • | • | • | • | • | • | • | • | |
| Resynch function | • | • | • | • | • | • | • | • | | • | • | |
| Max cutting with | 170 cm | 170 cm | 170 cm | 170 cm | 170 cm | 170 cm | 210 cm | 320 cm | 106,7 cm | 170 cm | 320 cm | |
| Min. cutting with | 28 cm | 28 cm | 28 cm | 28 cm | 28 cm | 28 cm | 28 cm | 50 cm | 60 cm | 28 cm | 28 cm | |
| X Cutting accuracy | | | | 1 mm | 1 mm | 1 mm | 1 mm | 1 mm | 1 mm | 1 mm | 1 mm | |
| Y Cutting accuracy | manually | 1 mm | 0,068 mm | 1 mm | 0,068 mm | 1 mm | 1 mm | 1 mm | 1 mm | 0,068 mm | 0,068 mm | |
| Max. Roller diameter allowed | Ø 26 cm | Ø 26 cm | Ø 26 cm | Ø 26 cm | Ø 26 cm | Ø 26 cm | Ø 26 cm | Ø 26 cm | Inline | Ø 26 cm | Ø 26 cm | |
| Max. Roll weight allowed | 80 Kg | 80 Kg | 80 Kg | 80 Kg | 80 Kg | 80 Kg | 80 Kg | 80 Kg | Inline | 80 Kg | 80 Kg | |
| Feed rate | 18 m/min | 18 m/min | 18 m/min | 18 m/min | 18 m/min | 34 m/min | 34 m/min | 34 m/min | 22 m/min | 18 m/min | 34 m/min | |
| Compressed air required | • | • | • | • | • | • | • | • | | • | • | |
| Accessories Machinery | • Inkluded + Optional | | | | | | | | | | | |
| FA10000 - JRU 170 | Max. 400 Kg Max. Ø 60 cm | Max. 400 Kg Max. Ø 60 cm | Max. 400 Kg Max. Ø 60 cm | Max. 400 Kg Max. Ø 60 cm | Max. 400 Kg Max. Ø 60 cm | Max. 400 Kg Max. Ø 60 cm | Max. 400 Kg Max. Ø 60 cm | | | | Max. 400 Kg Max. Ø 60 cm | |
| FA10002 - JRU 320 | | | | | | | | Max. 400 Kg Max. Ø 60 cm | Max. 400 Kg Max. Ø 60 cm | | Max. 400 Kg Max. Ø 60 cm | |
| FA00301/2 - REW 162 | | + | + | + | + | + | | | | + | + | |
| FA00182 - Winder 170 | | + | + | + | + | + | | | | + | | |
| FA00180 - Winder 320 | | | | | | | + | + | | | + | |
| FA00196 - Staker 170 | | + | + | + | + | + | | | | + | | |
| FA00183 - Zipper 320 | | | | | | | | + | | | + | |
| Heavy Duty acc. (no motor) | Max. 200 Kg Max. Ø 60 cm | Max. 200 Kg Max. Ø 60 cm | Max. 200 Kg Max. Ø 60 cm | Max. 200 Kg Max. Ø 60 cm | Max. 200 Kg Max. Ø 60 cm | Max. 200 Kg Max. Ø 60 cm | Max. 200 Kg Max. Ø 60 cm | Max. 200 Kg Max. Ø 60 cm | Max. 200 Kg Max. Ø 60 cm | | Max. 200 Kg Max. Ø 60 cm | Max. 200 Kg Max. Ø 60 cm |